

# NLM Pharmacy Refrigerator

## Features:

- Top mounted system
- TGA Approved
- E-Glass & Heated cabinet facia to prevent condensation up to 80% R.H.
- Five (5) rows of PVC coated shelves behind each door
- Castors
- Automatic water disposal
- Operating ambient temperature at 40°C
- Digital Display with Built in Alarms
- Hi / Lo Read Out



2°C to 8 °C



700 L

1000 L

1614 L

2170 L



870w x 700d x 1980h

1200w x 700d x 1980h

1880w x 700d x 1980h

2400w x 700d x 1980h



# Specifications

## Optional equipment



Temperature

Data Logger

Keypad

Model	NLM 700/1	NLM 1000/2	NLM 1614/3	NLM 2170/4
Capacity	700 L	1000 L	1614 L	2170 L
External Dimensions	870w x 700d x 1980h	1200w x 700d x 1980h	1880w x 700d x 1980h	2400w x 700d x 1980h
Internal Dimensions	770w x 550d x 1555h	1100w x 550d x 1555h	1780w x 550d x 1520h	2300w x 550d x 1520h
Weight	95 Kg	125 Kg	175 Kg	195 Kg
Voltage	240 V	240 V	240 V	240 V
Power Requirement	10 amp GPO	10 amp GPO	10 amp GPO	10 amp GPO
Watts	850W	1000W	1176W	1970W
Refrigerant	R134a	R134a	R134a	R134a
Warranty	12 Months*	12 Months*	12 Months*	12 Months*
Shelves size	750 x 530	1080 x 530	565 x 530	575 x 530
Number of Shelves	5	5	15	20
Digital Display	✓	✓	✓	✓
Castors	✓	✓	✓	✓
Int./Ext. Cabinet Finish	White Colourbond	White Colourbond	White Colourbond	White Colourbond
Insulation	50mm	50mm	50mm	50mm
High/Low Temperature Alarm	✓	✓	✓	✓
Fan Forced Refrigeration System	✓	✓	✓	✓
Door Lock	✓	✓	✓	✓
Solid Door / Glass Door	✓	✓	✓	✓
<b>Optional Equipment</b>				
Door ajar alarm	✓	✓	✓	✓
Port entry	✓	✓	✓	✓
Remote alarm	✓	✓	✓	✓
Temp alert	✓	✓	✓	✓
Independent data logger	✓	✓	✓	✓
Chart recorder	✓	✓	✓	✓
Battery backup for controller	✓	✓	✓	✓
Additional shelves	✓	✓	✓	✓

\*Refer to warranty sheet

Nuline Refrigeration reserves the right to alter the specifications without prior notice.